

AX1800 Dual Band Wi-Fi 6 GPON Router

MODEL:XX230v



Overview

Compliant with the ITU-T G.984 GPON standards, XX230v supports maximum data rates of up to 2.488Gbps downstream and 1.244Gbps upstream. Along with a 10/100/1,000Mbps WAN/LAN port and 3 10/100/1,000Mbps LAN ports, users can enjoy high-speed GPON services and bandwidth-intensive multimedia applications—such as interactive gaming, streaming, and real-time video—much faster and easier than ever before.



802.11ax Technology

Create a seamless Wi-Fi network in your home with the revolutionary combination of OFDMA, MU-MIMO, and Beamforming technologies



Ultimate Wireless Speed

Combined wireless speeds of up to 574 Mbps (over 2.4 GHz) and 1201 Mbps (over 5 GHz)



Supports EasyMesh

Adopts EasyMesh technology, which has further improved and standardized Wi-Fi functions, such as Wi-Fi diagnostics, channel selection and traffic separation



Easy Remote Management

Supports Aginet APP, OMCI, TR-069, TR-098, and TR181 now and can be upgraded through software to support TAUC cloud management.

Features



AX1800 Dual-Band Wi-Fi 6

1201 Mbps (5 GHz) +
574 Mbps (2.4 GHz)



VoIP Telephony


Support VoIP base functions




Full Gigabit Ports and USB 2.0

1x GE WAN/LAN + 3x GE LAN
+ 1x FXS + 1x USB 2.0 ports

Network Topology



Hardware Description



Specifications

Hardware

- **Interface**
 - 1 10/100/1000 Mbps WAN/LAN Port,
 - 3 10/100/1000 Mbps LAN Ports,
 - 1 USB 2.0 Port, 1 FXS Port, 1 SC/APC GPON Port
- **Button**
 - Power On/Off Button, WPS/Wi-Fi Button, Reset Button
- **External Power Supply**
 - 12V/1.5A
- **Dimensions (W * D * H)**
 - 10.2 × 5.3 × 16.4 in (260.2 × 135.0 × 416 mm)
- **Antenna**
 - 4 High-Performance External Antennas

Wireless

- **Wireless Standards**
 - IEEE 802.11a/n/ac/ax 5 GHz, IEEE 802.11b/g/n/ax 2.4 GHz
- **Frequency**
 - 2.4 GHz and 5 GHz
- **Signal Rate**
 - 1201 Mbps at 5 GHz, 574 Mbps at 2.4 GHz
- **Transmit Power**
 - EU: <20 dBm (2.4 GHz), <23 dBm (5 GHz)
 - US: <26 dBm (2.4 GHz), <28 dBm (5 GHz)
- **Wireless Function**
 - Enable/Disable Wireless Radio, Wireless Schedule, WMM, Wireless Statistics
- **Mesh**
 - EasyMesh, IEEE 802.11k/v/r, Self-healing, Seamless Roaming
- **Wireless Security**
 - WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA2 PSK/WPA PSK mixed mode 802.1x(WPA2 Enterprise)
- **Wireless Schedule**
 - Support 2.4 GHz and 5 GHz Wireless Schedule

Others

- **Certification**
 - CE
- **Environment**
 - Operating Temperature: 0°C~40°C (32°F~104°F),
 - Storage Temperature: -40°C~60°C (-40°F ~140°F)
- **Package Contents**
 - AX1800 Dual-Band Wi-Fi 6 GPON Router XX230v
 - Power Adapter
 - RJ45 Ethernet Cable
 - Quick Installation Guide

Software

- **DHCP**
 - Server, DHCP Client List, Address Reservation
- **Quality of Service**
 - Hardware QoS, Flow Classification
- **VPN Server**
 - PPTP VPN, IPSec VPN, OpenVPN
- **Firewall Security**
 - DoS, IPv4 SPI Firewall, IPv6 Firewall, IP and MAC Address Binding, Access Control
- **Dynamic DNS**
 - TP-Link, DynDns, NO-IP
- **Protocols**
 - IPv4, IPv6
- **USB**
 - Samba, FTP, DLNA Server
- **Management**
 - Local Management, Remote Management, Aginet APP, TR069(TR-098/TR-181)
- **Advanced Functions**
 - VoIP, Parental Controls, Port Forwarding, TX Beamforming, MU-MIMO, supports IGMP Proxy V1/V2/V3 and IGMP Snooping, Airtime Fairness, Band Steering, Multi-SSID, Wi-Fi Schedule

General Specifications

- **GPON**
 - ITU G. 984 standard, Class B+
 - 2.488Gbps downstream/1.244Gbps upstream
- **Wavelength**
 - 1490nm downstream/1310nm upstream
- **Receiving sensitivity**
 - GPON: -27dBm
- **Saturated power**
 - GPON: -8dBm
- **Transmitting power**
 - GPON: 0.5~5dBm
- **Transmitter**
 - DFB Laser
- **Receiver**
 - PIN-TIA
- **Distance**
 - 0 ~ 20Km Max