# U/UTP LSZH Category 6 Eca

**U/UTP Category 6, 4 pairs, LSZH box**



**Nexans Ref.:** 10566833
**Country Ref.:** TR
**EAN 13:** 8680969823692

## CONTACT

Sales & Marketing
Phone: +90 212 266 0160
alper.altinok@nexans.com

- Complies to latest Cat 6 standard version
- Guaranteed performance to 250MHz
- Patented central cross technology for maintaining geometry and performance
- Supports Gigabit Ethernet
- RoHS EC Directive 2011/65/EU compliant
- LSZH sheathed

## STANDARDS

**Product** ANSI/TIA-568-C.2; EN 50173-1; IEC 61156-5

**International** ISO/IEC 11801

## APPLICATION

Nexans U/UTP Category 6 cables are the standard 250MHz offering from Nexans. Manufactured in accordance with TIA/EIA 568-C.2, EN 50173-1, ISO/IEC 11801 and IEC 61156-5 requirements,U/UTP cable is the best choice to support all Class E applications like Ethernet, Fast Ethernet, Gigabit Ethernet, ..., The Cat 6 U/UTP cables are suitable for basic voice and data installations up to 250 MHz. Nexans Category 6 cables are compliant with the requirements of the TIA/EIA 568-C, EN 50173-1, ISO/IEC 11801 and IEC 61156-5.

### Performance

Used with Cat 6 connectivity, these cables are compliant with Class E linkrequirements as described in EN 50173 and ISO 11801 standards.

### Features

- Central cross for improved geometry and performance
- Central cross member reduces risk of crushing or kinking
- Compact design for minimum volume in ducts or trails.
- LSZH sheath
- Design for easy and quick installation
- UTP construction
- Supports Gigabit Ethernet
- RoHS EC Directive 2011/65/EU compliant
- Complies to latest Cat 6 standards



Halogen free
-


Ambient installation T°C range
**0 ... 50 °C**


Flame retardant
**IEC 60332-1**


Gases corrosivity
-



Min. dynamic operating bending rad.
**24.0 mm**



Static bending rad.
**48 mm**


Operating temp.
**-20 ... 60 °C**


Smoke density
-



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

# U/UTP LSZH Category 6 Eca

**U/UTP Category 6, 4 pairs, LSZH box**

## CHARACTERISTICS

| | |
|---|---|
| **Construction characteristics** | |
| Type of cable | U/UTP |
| Outer sheath | LSZH |
| Colour | Orange |
| Halogen free | - |
| **Dimensional characteristics** | |
| Approximate weight | 38 kg/km |
| Diameter over insulation | 0.97 mm |
| Nominal outer diameter | 6.0 mm |
| **Electrical characteristics** | |
| Characteristic impedance | 100 Ohm |
| Max. DC resistance of the conductor at 20°C | 93.8 Ohm/km |
| Mutual capacitance | 56 nF/km |
| **Transmission characteristics** | |
| Attenuation, max. 250 MHz | 32.8 dB/100m |
| Attenuation Crosstalk Ratio, 250MHz | 5.5 dB/100m |
| Powersum Near End Crosstalk, 250MHz | 36.3 dB |
| Powersum Equal Level Far End Crosstalk, 250MHz | 19 dB |
| Return loss, 250MHz | 17.3 dB |
| Coupling attenuation at 30 MHz | 45 dB |
| Near End Crosstalk @ 250 MHz | 39.3 dB |
| Nominal Velocity of Propagation (NVP) | 68 % |
| Propagation delay, max. 100 MHz | 536 ns/100m |
| Skew | 45 ns/100m |
| **Usage characteristics** | |
| Packaging | Box |
| Length | 100 m |
| Ambient installation temperature, range | 0 ... 50 °C |
| Category | Cat. 6 |
| Component function | Cable |
| Flame retardant | IEC 60332-1 |
| Gases corrosivity | - |
| Minimum dynamic operating bending radius | 24.0 mm |
| Minimum static operating bending radius | 48 mm |
| Operating temperature, range | -20 ... 60 °C |
| Smoke density | - |



All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.