

Overview

WS- C2960-24PC-L is one of the Cisco Catalyst 2960 Series switches. This series support voice, video, data, and highly secure access. They also deliver scalable management as your business needs change. The Common Features are included: Enhanced security including Cisco TrustSec for providing authentication, access control, and security policy administration, Multiple Fast or Gigabit Ethernet performance options, Cisco EnergyWise for power management, Scalable network management.

Quick Specs

Figure 1 shows the appearance of the WS-C2960-24PC-L.



Table 1 shows the Quick Spec of the WS-C2960-24PC-L.

Product Code	WS-C2960-24PC-L
Enclosure Type	Rack-mountable - 1U
Feature Set	LAN Base
Uplink Interfaces	2 dual-purpose (10/100/1000 or SFP) ports
Ports	24 x Ethernet 10/100 PoE ports
Throughput	6.5 Mpps
Backplane Capacity	16 Gbps
DRAM	64 MB
Dimensions	1.73 x 17.5 x 9.3 in.
Package Weight	9.5 Kg

Product Details


Figure 2 shows the front panel of the Cisco 2960-24PC-L switch.



Note:

(1)	LED Area
(2)	24 x Ethernet 10/100 PoE ports
(3)	2 dual-purpose uplinks

Figure 3 shows the back panel of the WS-C2960-24PC-L.



Note:

(1)	RJ45 Console Port	(3)	RPS Connector
(2)	Fan Exhaust	(4)	AC power connector

## The Accessories

Table 2 shows some accessories of the WS-C2960-24PC-L.

Models	Description
<a href="#">GLC-LH-SM</a>	GE SFP, LC connector LX/LH transceiver
<a href="#">GLC-SX-MMD</a>	1000BASE-SX SFP transceiver module, MMF, 850nm, DOM
<a href="#">CAB-CONSOLE-RJ45</a>	Console Cable 6ft with RJ45 and DB9F

## Compare to Similar Items

Table 3 shows the comparison of similar items.

Models	WS-C2960-24PC-L	<a href="#">WS-C2960-24TC-L</a>
PoE Available	Yes	N/A
Ports	24 x Ethernet 10/100 PoE ports	24 x Ethernet 10/100 ports
Uplinks	2 dual-purpose uplinks	2 dual-purpose uplinks
Feature Set	LAN Base	LAN Base

Get more information

Do you have any question about the Cisco Catalyst C2960-24PC-L switch?

Contact us now via [Live Chat](#) or [sales@router-switch.com](mailto:sales@router-switch.com).




Specification

WS-C2960-24PC-L Specification	
Type	Fixed
Topology	Ethernet (10/100BaseTX) Ethernet (10/100/1000BaseT) Gigabit Ethernet (SFP)
Maximum Port density	24 10/100 PoE ports
Uplinks	2 dual-purpose (10/100/1000 or SFP) ports
Modular/Expansion Slots	n/a
Architecture	Layer 2 Switching (basic connectivity), Layer 2 Switching (intelligent services), Voice Enabled
Form Factor	Fixed, Rack Mountable, Standalone/Clustering
Dimensions	1.73 x 17.5 x 13 in.
DRAM	64 MB
Features	
Specialized Service Modules	n/a
Security	
DHCP Snooping	
Dynamic ARP Inspection	
IP Source Guard	
RP Rate Limiters	
TCP Intercept	
802.1x	
Port Security	
Dynamic VLANs	
Private VLANs	
Private VLAN Edge	

Secure Shell	
SNMPv3	
Unicast RPF	
ACLs (L2-L4)	
Kerberos	
TACACS+	
RADIUS	
High Availability/Resiliency	
Hardware Redundancy	External Redundant Power Supply
High Availability/Resiliency	PVST, Broadcast Suppression, Unicast Suppression, Multicast Suppression, Spanning Tree, Portfast, Uplink Fast, Backbone Fast, 802.1s, 802.1w
Management	
Management features	SPAN, RSPAN, CiscoView, Cisco Discover Protocol (CDP), Virtual Trunking Protocol (VTP), Telnet Client, BOOTP, TFTP, CiscoWorks, CWSI, RMON, SNMP, Clustering, Web-Based Management
Scalability	
WAN Interface Support	n/a
Throughput	6.5 Mpps
Backplane Capacity	16 Gbps
Number of VLANs	255

## Download Resource

### Transition Guide

-  [Cisco Catalyst 2960/2960-SF/2960-S Series Transition Guide](#)
-  [Guide to Upgrade Cisco Access and Backbone Switch](#)
-  [Selecting Cisco Switches-Campus, Branch, Digital Building](#)

## Want to Buy

Order Now

Get a Quote

## Why Router-switch.com


As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.


200+


18,000+


\$20,000,000


50%-98%


100%

## Contact Us

---

- Tel: +1-626-239-8066 (USA) 852-30691898/ 852-30691868 (Hong Kong)
- Fax: 852-30691898 (Hong Kong)
- Email: [sales@router-switch.com](mailto:sales@router-switch.com)