

Get a Quote

Overview

- 24 Ethernet 10/100 ports
- 2 SFP-based Gigabit Ethernet ports
- 32-Gbps, high-speed stacking bus
- Innovative stacking technology
- 1 RU stackable, multilayer switch
- Enterprise-class intelligent services delivered to the network edge

Specification

WS-C3750-24TS-S data sheet	
Manufacturer	Cisco Systems, Inc
Manufacturer Part Number	WS-C3750-24TS-S
Product Type	Managed, Stackable 24 ports L3 Switch
Form Factor	Fixed, Rack Mountable 1U, Stackable/Clustering
Switch Port density - Uplinks	24 x 10/100 + 2 x SFP
MAC Address Table Size	12K entries
Max Number of Stacks	9
Routing Protocol	RIP-1, RIP-2, EIGRP, static IP routing, RIPng
Remote Management Protocol	SNMP 1, RMON 1, RMON 2, RMON 3, RMON 9, Telnet, SNMP 3, SNMP 2c, HTTP, SSH
Authentication Method	Kerberos, Secure Shell (SSH), RADIUS, TACACS+
Features	Flow control, full duplex capability, Layer 3 switching, auto-sensing per device, IP-routing, DHCP support, auto-negotiation, ARP support, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, traffic shaping, stackable, IPv6 support, Trivial File Transfer Protocol (TFTP) support, Access Control List (ACL) support, Quality of Service (QoS)
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.3ae, IEEE 802.1s
DRAM Memory	128 MB
Flash Memory	16 MB Flash
LED Status Lights Indicators	Port status, link activity, port transmission speed, port duplex mode, bandwidth utilization %, status
Connectivity / Expansion Slots	

Interfaces	24 x 10Base-T/100Base-TX - RJ-45 1 x console - RJ-45 - management Network stack device : 1 x x 2 2 x SFP (mini-GBIC)
Power Supply Specifications	
Power Device	Power supply - internal
Voltage Required	AC 120/230 V (50/60 Hz)
Power Consumption Operational	45 Watt
Features	Redundant Power System (RPS) connector
Dimensions / Weight / Miscellaneous	
Width	44.5 cm
Depth	30 cm
Height	4.4 cm
Weight	3.6 kg
MTBF	294,928 hour(s)
Compliant Standards	CE, TUV GS, BSMI CNS 13438 Class A, CISPR 24, EN 60950, EN55022, VCCI Class A ITE, IEC 60950, EN55024, UL 60950 Third Edition, CISPR 22, CB, AS/NZ 3548 Class A, MIC, CSA C22.2 No. 60950 Third Edition
System Software	
Software Included	Cisco IOS IP Base
Manufacturer Warranty	
Service & Support	Limited lifetime warranty
Service & Support Details	Limited warranty - lifetime

Want to Buy

[Order Now](#)
[Get a Quote](#)

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of [Cisco](#), [Huawei](#), [HPE](#), [Dell](#), [Hikvision](#), [Juniper](#), [Fortinet](#), etc.



200+

Countries we Sold



18,000+

Customers Trusted



\$20,000,000

Inventory Available



50%-98%

Off Global List Price



100%

Safe Online Shopping

Contact Us

- Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com