CP-7962G Datasheet





Overview

Cisco unified IP phone CP-7962G is designed to support wideband voice performance to meet the needs for cooperation managers or administrative. CP-7962 is the part of a new suite of evolutionary Cisco Unified IP phone 7900 Series endpoint. The phone has full-feature IP phone system with speakerphone, handset. The phone can also easily lead you through all call features and functions via 6 programmable and 4 interactive soft keys. The 5-inch, high resolution graphical grayscale LCD panel on the phone displays the information about time, data, callers and status. The setting key allows user to adjust display from background template, and select ringer sounds through the user Preference menu. Network Configuration preferences also can be set up (usually by the system administrator). Services key allows users to quickly access diverse information such as weather, stocks, quote of the day, or any Web-based information using XML.

*Note: The phone can be powered by either POE Ethernet switch or phone power supply, the power supply does not include by default, customer need to purchase separately.

Specification

model info	CP-7962G
product Type	IP phone
Codec Support	G.711a, G.711μ, G.729a, G.729ab, G.722, and iLBC audio compression codecs are supported
Speakerphone	Full-duplex speakerphone with acoustic echo cancellation.
Messages Key	Provide direct access to voicemail
Directories Key	Corporate directory integrates with the Lightweight Directory Access Protocol Version 3 (LDAP3) standard directory.
Settings Key	preferences also can be set up (usually by the system administrator). Configuration can be set up either automatically or manually for Dynamic Host Control Protocol (DHCP), Trivial File Transfer Protocol (TFTP), Cisco Unified Communications Manager, and backup Cisco Unified Communications Manager instances. Other available Settings submenus include Device Configuration, Security Configuration, and Model Information.
Help Button	Online Help gives users information about the phone keys, buttons and features
Expansion Module Support	An optional add-on module, the Cisco Unified IP Phone Expansion Module 7914, provides 14 additional buttons for programming directory numbers or speed dials. Up to two expansion modules can be used.
Mutiple Ring Tones	More than 24 defined user-selectable ring tones are available. Ring tones may also be personalized through use of the Cisco Unified Phone Application Suite.
Language Support	morethan 30 languages.
Dimensions (H x W x D)	8.2 x 10.5 x 6 in. (20.32 x 26.67 x 15.24 cm)
Weight	3.5 lb (1.6 KG)
Phone Software Requirements	Supported in 8.3(2) and greater
Call Control compatibility	Supported in Cisco Unified Communications Manager Versions 4.1(3)sr5b, 4.2(3)sr2b, 4.3(1), 5.1.1(b), 5.1(2), 6.0(1) and greater Supported in Cisco Unified Communications Express and SRST Version 4.1
Signaling protocols	Skinny Client Control Protocol (SCCP) and Session Initiation Protocol (SIP) with Cisco call control
license	SW-CCME-UL-7962: Communications Manager Express License For One 7962G Phone

Want to Buy

Why Router-switch.com

As a leading network hardware supplier, Router-switch.com focuses on original new ICT equipment of Cisco, Huawei, HPE, Dell, Hikvision, Juniper, Fortinet, etc.











Contact Us

• Tel: +1-626-655-0998 (USA) +852-3050-1066 / +852-3174-6166

Fax: +852-3050-1066 (Hong Kong)Email: sales@router-switch.com