



Cisco SFP GLC Module Datasheet



Router-Switch.com
Leading Network Hardware Supplier

CONTENT

Overview	2
Appearance	2
Key Features and Benefits	2
Product Specifications	3
Basic Ordering Information.....	4
Additional information	9
Where to buy	9
Sources.....	9

Contact Us

Tel: +1-626-239-8066 (USA) +852-3050-1066 / +852-3174-6166 /

Fax: +852-3050-1066 (Hong Kong)

Email: cisco@router-switch.com (Sales Inquiries)

ccie-support@router-switch.com (CCIE Technical Support)

OVERVIEW

Cisco SFPs can meet Cisco users' different needs, GLC-SX-MMD, the 1000BASE-SX SFP, can support up to 1km over laser-optimized 50 μ m multimode fiber cable; GLC-LH-SM, Cisco 1000BASE-LX/LH SFP transceiver module, operates on standard single-mode fiber-optic link spans of up to 10 km and up to 550 m on any multimode fibers; GLC-T over unshielded twisted pair (UTP) Category 5 Cable, etc. Cisco SFP+(the 10G fiber optical module) can connect with other type of 10G modules. SFP-10G-SR, used for high-speed data transmission applications, supports 300m by MMF; SFP-10G-LRM supports 220m on standard FDDI grade multimode fiber (MMF) and 300m on standard single-mode fiber (SMF, G.652); SFP-10G-LR, supports 10 km on standard single-mode fiber (SMF, G.652). See more detailed modules as follow, comes with best price and a good warranty.

APPEARANCE

Figure 1. CISCO SFP GLC MODULE



KEY FEATURES AND BENEFITS

- **Hot swappable to maximize uptime and simplify serviceability**
- **Flexibility of media and interface choice on a port-by-port basis, so you can “pay as you populate”**
- **Robust design for enhanced reliability**
- **Supports digital optical monitoring (DOM) capability**

PRODUCT SPECIFICATIONS OF CISCO SFP GLC MODULE

Product	Wavelength (nm)	Fiber Type	Core Size (μm)	Modal Bandwidth (MHz* Km)***	Operating Distance (m)
1000BASE-SX	850	MMF	62.5	160 (FDDI-grade)	220 (722 ft)
			62.5	200 (OM1)	275 (902 ft)
			50	400 (400/400)	500 (1,640 ft)
			50	500 (OM2)	550 (1,804 ft)
			50	2000 (OM3)	1000 (3281 ft)
1000BASE-LX/LH	1310	MMF*	62.5	500	550 (1,804 ft)
			50	400	550 (1,804 ft)
			50	500	550 (1,804 ft)
		SMF	_**	-	10,000 (32,821 ft)
1000BASE-EX	1310	SMF	_**	-	40,000 (131,234 ft)
1000BASE-ZX	1550	SMF	-	-	Approximately 70 km depending on link loss
1000BASE-BX-U	1310	SMF	_**	-	10,000 (32,821 ft)
1000BASE-BX-D	1490	SMF	_**	-	10,000 (32,821 ft)
GLC-BX40-D-I	1550	SMF	_**	-	40,000 (131,234 ft)
GLC-BX40-DA-I	1490	SMF	_**	-	40,000 (131,234 ft)
GLC-BX40-U-I	1310	SMF	_**	-	40,000 (131,234 ft)
GLC-BX80-D-I	1570	SMF	_**	-	80,000 (262,467 ft)

GLC-BX80-U-I	1490	SMF	._**	-	80,000 (262,467 ft)
GLC-GE-DR-LX	1310	SMF	._**	-	10,000 (32,821 ft)

* A mode-conditioning patch cord, as specified by the IEEE standard, is required regardless of the span length. Note how the mode conditioning patch cord for 62.5- μ m fibers has a different specification from the mode-conditioning patch cord for 50- μ m fibers.

** ITU-T G.652 SMF as specified by the IEEE 802.3z standard.

*** Specified at transmission wavelength.

CISCO SFP GLC MODULE BASIC ORDERING INFORMATION

Description	Model
1000BASE-T SFP	GLC-T
GE SFP, LC connector SX transceiver	GLC-SX-MM
GE SFP, LC connector LX/LH transceiver	GLC-LH-SM
1000BASE-ZX SFP	GLC-ZX-SM
1000BASE-BX SFP, 1490NM	GLC-BX-D
1000BASE-BX SFP, 1310NM	GLC-BX-U
100BASE-FX SFP for FE port	GLC-FE-100FX
100BASE-LX SFP for FE port	GLC-FE-100LX
100BASE-BX10-U SFP	GLC-FE-100BX-U
100BASE-BX10-D SFP	GLC-FE-100BX-D
100BASE-EX SFP (40km)	GLC-FE-100EX
100BASE-ZX SFP (80km)	GLC-FE-100ZX

1000BASE-T SFP (NEBS 3 ESD)	SFP-GE-T
1000BASE-LX/LH SFP (DOM)	SFP-GE-L
1000BASE-SX SFP (DOM)	SFP-GE-S
1000BASE-ZX Gigabit Ethernet SFP (DOM)	SFP-GE-Z
OC3/STM1 SFP, Multi-mode fiber	SFP-OC3-MM
OC3/STM1 SFP, Single-mode fiber, Short Reach	SFP-OC3-SR
OC3/STM1 SFP, Single-mode fiber, Intermediate Reach	SFP-OC3-IR1
OC3/STM1 SFP, Single-mode fiber, Long Reach (40km)	SFP-OC3-LR1
OC3/STM1 SFP, Single-mode fiber, Long Reach (80km)	SFP-OC3-LR2
OC-12/ STM-4 SFP, Multi-mode Fiber	SFP-OC12-MM
OC12/STM4 SFP, Short Reach	SFP-OC12-SR
OC-12/ STM-4 SFP, Intermediate Reach (15km)	SFP-OC12-IR1
OC-12/ STM-4 SFP, Long Reach (40km)	SFP-OC12-LR1
OC-12/ STM-4 SFP, Long Reach (80km)	SFP-OC12-LR2
OC-48c/STM-16c	SFP-OC48-IR1
OC-48c/STM-16c SFP, Long Reach (80km)	SFP-OC48-LR2
CWDM 1470 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1470
CWDM 1490 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1490
CWDM 1510 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1510

CWDM 1530 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1530
CWDM 1550 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1550
CWDM 1570 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1570
CWDM 1590 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1590
CWDM 1610 NM SFP Gigabit Ethernet and 1G/2G FC	CWDM-SFP-1610
10GBASE-LR SFP+ Module for SMF 10 Gbps	SFP-10G-LR HW
10GBASE-SR SFP Module	SFP-10G-SR
Cisco GLC-FE-100FX-RGD 100Base-FX Multi Mode Rugged SFP	GLC-FE-100FX-RGD
Cisco GLC-FE-100LX-RGD 100Mbps Single Mode Rugged SFP	GLC-FE-100LX-RGD
Cisco GLC-SX-MM-RGD 1000Mbps Multi-Mode Rugged SFP	GLC-SX-MM-RGD
Cisco GLC-LX-SM-RGD 1000Mbps Single Mode Rugged SFP	GLC-LX-SM-RGD
Cisco GLC-ZX-SM-RGD 1000BASE-ZX Single Mode Rugged SFP	GLC-ZX-SM-RGD
Cisco GLC-EX-SMD GE SFP, LC Connector, EX transceiver	GLC-EX-SMD
Cisco GLC-SX-MMD 1000BASE-SX SFP transceiver module, MMF, 850nm, DOM	GLC-SX-MMD
Cisco GLC-ZX-SMD 1000BASE-ZX SFP transceiver module, SMF, 1550nm, DOM	GLC-ZX-SMD
Cisco GLC-LH-SMD 1000BASE-LX/LH SFP transceiver module, MMF/SMF, 1310nm, DOM	GLC-LH-SMD
10GBASE-LRM SFP Module	SFP-10G-LRM

SFP+ transceiver module, 8.5 Gbps, MDS9000, Fabric Channel	DS-SFP-FC8G-SW
OC-48c/STM-16c SFP, Short Reach	SFP-OC48-SR
SFP-10G-SR-X= 10GBASE-SR SFP Module, LC connector, 850nm, 300m range, multimode fiber (MMF), extended operating temperature range	SFP-10G-SR-X=
10GBASE-SR SFP Module, Enterprise-Class	SFP-10G-SR-S
1000BASE-BX10 SFP module for single-strand SMF, 1550-nm TX/1310-nm RX wavelength, single LC/PC connector	GLC-BX40-D-I
1000BASE-BX10 SFP module for single-strand SMF, 1310-nm TX/1550-nm RX wavelength, single LC/PC connector	GLC-BX40-U-I
1000BASE-BX10 SFP module for single-strand SMF, 1570-nm TX/1490-nm RX wavelength, single LC/PC connector	GLC-BX80-D-I
1000BASE-BX10 SFP module for single-strand SMF, 1490-nm TX/1570-nm RX wavelength, single LC/PC connector	GLC-BX80-U-I
1000BASE-BX10 SFP module for single-strand SMF, 1490-nm TX/1310-nm RX wavelength, single LC/PC connector	GLC-BX40-DA-I
Dual-channel 1000BASE-BX10 SFP module for single-strand SMF, 1490-nm TX/1310-nm RX wavelength, two single LC/PC connectors	GLC-2BX-D=
Gigabit passive optical network (GPON) Class B+ SFP OLT transceiver module, 1490-nm TX/1310-nm RX wavelength	SFP-GPON-B
Gigabit passive optical network (GPON) Class B+ SFP OLT transceiver module, 1490-nm TX/1310-nm RX wavelength, industrial temperature range	SFP-GPON-B-I
Gigabit passive optical network (GPON) Class C+ SFP OLT transceiver module, 1490-nm TX/1310-nm RX wavelength	SFP-GPON-C

Gigabit passive optical network (GPON) Class C+ SFP OLT transceiver module, 1490-nm TX/1310-nm RX wavelength, industrial temperature range	SFP-GPON-C-I
1000BASE-T SFP transceiver module for Category 5 copper wire	GLC-TE
1000BASE-T SFP	GLC-TE++=
QSFP to SFP10G adapter	CVR-QSFP-SFP10G
X2 to SFP+ Adaptor module	CVR-X2-SFP10G
16 Gbps Fibre Channel SW SFP+, LC	DS-SFP-FC16G-SW
QSFP40G BiDi Short-reach Transceiver	QSFP-40G-SR-BD HW
QSFP 40GBASE-LR4 Trnscvr Mod. LC. 10km. Enterprise-Class	QSFP-40G-LR4-S
4 Gbps Fibre Channel-SW SFP. LC. 4 pack. Spare	DS-SFP-4G-SW-4=
40GBASE-SR4 (IEEE 802.3ba Spec.) QSFP+ transceiver module for MMF, MPO/MTP connector	QSFP-40G-SR4-S=
40GBASE-LR4 QSFP transceiver module for SMF, duplex LC connector, up to 2km	WSP-Q40GLR4L
40GBASE-LR4 QSFP+ transceiver module for SMF, duplex LC connector, 10km reach	QSFP-40GE-LR4-S
40GBASE-LR4 QSFP+ transceiver module for SMF, 4 CWDM lanes in 1310nm window Mixed inside module, duplex LC connector, 10km reach	QSFP-40GE-LR4
QSFP 4x10GBASE-SR Transceiver Module, MPO, 300M	QSFP-40G-CSR4
Cisco 10GBASE-ER SFP+ Module for SMF	SFP-10G-ER
40GBASE-SR4 QSFP Transceiver Module with MPO Connector	QSFP-40G-SR4

Cisco 10GBASE-ZR SFP10G Module for SMF	SFP-10G-ZR
--	----------------------------

ADDITIONAL INFORMATION

[Features and Benefits of Cisco 25G, QSFP and QSFP28 Modules](#)

[Upgrade Seamlessly From 40Gb or 10Gb-Cisco 40/100Gb QSFP100 BiDi Pluggable Transceiver](#)

[What Are SFP Ports Used For?](#)

[GLC-T vs. SFP-GE-T](#)

[Cisco XFP vs. SFP vs. SFP+](#)

[Cisco SFP vs. GBIC vs. XEP vs. SFP Plus](#)

[Cisco Transceiver Modules Overview & the Latest SFP Transceivers](#)

WHERE TO BUY

Want to buy this series of products? please contact:

- Tel: +1-626-239-8066 (USA)/ +852-3050-1066 / +852-3174-6166
- Fax: +852-3050-1066 (Hong Kong)
- Email: sales@router-switch.com (Sales Inquiries)

Or visit: [Cisco SFP GLC Modules](#)

About us

Router-switch.com (HongKong Yejian Technologies Co., Ltd), founded in 2002, is one of the biggest Global Network Hardware Supplier. We are a leading provider of network products with 14,500+ customers in over 200 countries. We provide original new and used network equipments (Cisco, Huawei, HPE, Dell, Hikvision, Juniper, EMC, etc.), including Routers, Switches, Servers, and all kinds of network solutions related products.

SOURCES

https://www.cisco.com/c/en/us/products/collateral/interfaces-modules/gigabit-ethernet-gbic-sfp-modules/product_data_sheet0900aecd8033f885.html